



**Soltec**

The professional power people

## ALP-BC series

### Rectifier/Battery Charger 10-1100A

#### Features

- Input surge protection
- EMI suppression
- True galvanic isolation
- Plug & Play modular design
- Multi-CPU design
- Protection against misuse
- Intelligent fan speed control
- High reliability and stability for harsh environment




# ALP-BC series Rectifier/Battery Charger 10-1100A



## Specification

RECTIFIER	
Input Voltage	3P3W, 3P4W or Single phase 208/220/380/400/415/480/600Vac (Special voltage can be customized)
Input Range	Around $\pm 20\%$
Input Frequency	50/60Hz $\pm 7\%$
DC OUTPUT	
Voltage Range	24V, 48V, 110V, 220V, 348Vdc (can be customized)
Current	10~1100A (can be customized)
OVERALL CHARACTERISTICS	
Temperature	0 - 40 °C (32 - 104 °F)
Humidity	0-90% (non-condensing)
Altitude	< 1500M above sea level
Short Circuit Protection	NFB
Lightning	MOV
LED, LCD, Buzzer	Yes
Dry Contact	Yes

\* All specifications mentioned above are subject to change without prior notice



**Soltec**  
The professional power people

### SOLTEC POWER CO., LTD

No.37,Yunke Road,Sec.3,Douliu City,Yunlin,Taiwan

Tel: +886-5-551-1017 Fax: +886-5-551-0027

<http://www.soltec.com.tw> E-mail: [soltec@soltec.com.tw](mailto:soltec@soltec.com.tw)

[sales@soltec.com.tw](mailto:sales@soltec.com.tw)