



Soltec

The professional power people

ATS-115 (1U)

Automatic Transfer Switch - 15A



Features

- Multiple microprocessor design
- LED and LCD display for status and data of ATS
- Output sockets can be independently controlled ON/OFF and scheduling
- To give a name for output socket and to delay setting switch
- Output sockets can be set to priority
- Remote monitoring with SNMP intelligent slot and RS-232 interface
- To get UPS current state through exclusive interface connects UPS
- Light weight, compact size, easy to transport and installation

ATS-115(1U)

Automatic Transfer Switch - 15A



Specification

MODEL	ATS-115
INPUT	
Source	Dual input (Line 1 and Line2)
Mode	1P2W+G
Rated Voltage	110Vac or 220Vac
Nominal Current	15A
Rated Frequency	50Hz or 60Hz
Voltage Range	80Vac ~ 275Vac
Frequency	Rated frequency \pm 5Hz
OUTPUT	
Socket	6pcs NEMA socket or 6pcs IEC socket
TRANSFER	
Time	< 6ms
Voltage Range	90Vac ~ 132Vac / 180Vac ~ 265Vac
Auto-switching Condition	Same frequency & phase polarity
INDICATOR	
LED	Normal (Green) ; Warning (Yellow)
LCD	I/P & O/P voltage, status, load Display data for each output socket <current; name> Displays input source / voltage / frequency / status Parameter setting / socket switch
INTERFACE	
UPS Communication	2 sets RS232 input
Foreign Communication	USB*1pcs; Intelligent slot* 1pc
Operation Temperature	0 - 40 °C (32 - 104 °F)
Relative Humidity	< 95% (non-condensing)
Altitudes	< 3000M
Dimensions(W*H*D)mm	440*44*250
Net Weight(kg)	4

* All specifications mentioned above are subject to change without prior notice



Soltec
The professional power people

SOLTEC POWER CO., LTD

No.37,Yunke Road,Sec.3,Douliu City,Yunlin,Taiwan

TeL:+886-5-551-1017 Fax:+886-5-551-0027

http://www.soltec.com.tw E-mail: soltec@soltec.com.tw

sales@soltec.com.tw